

Total integrity for the most demanding applications



EASTERN SEALS
GLOBAL SEALING PROVIDER

ES – FEP Encapsulated Kamlock™ Gaskets

Coupling Size		Gasket Dimensions (inches)			Gasket Dimensions (mm)		
Inches	mm	OD	ID	Cross-Section	OD	ID	Cross-Section
0.5	12.7	1.024 (±.020)	0.669 (±.020)	0.157 (±.006)	26.00 (±0.51)	17.00 (±0.51)	4.00 (±0.15)
0.75	19	1.375 (±.025)	0.875 (±.020)	0.218 (±.006)	35.00 (±0.63)	22.20 (±0.63)	5.54 (±0.15)
1	25.4	1.563 (±.025)	1.063 (±.025)	0.250 (±.006)	39.70 (±0.63)	27.00 (±0.63)	6.35 (±0.15)
1.25	31.7	1.938 (±.030)	1.359 (±.030)	0.250 (±.006)	49.20 (±0.76)	34.50 (±0.76)	6.35 (±0.15)
1.5	38	2.188 (±.035)	1.625 (±.035)	0.250 (±.006)	55.60 (±0.89)	41.30 (±0.89)	6.35 (±0.15)
2	50.8	2.625 (±.035)	2.000 (±.035)	0.250 (±.006)	66.70 (±0.89)	50.80 (±0.89)	6.35 (±0.15)
2.5	63.5	3.125 (±.035)	2.375 (±.035)	0.250 (±.006)	79.40 (±0.89)	60.30 (±0.89)	6.35 (±0.15)
3	76.2	3.719 (±.040)	3.000 (±.040)	0.250 (±.006)	94.50 (±1.02)	76.20 (±1.02)	6.35 (±0.15)
4	101.6	4.875 (±.040)	4.000 (±.040)	0.250 (±.006)	123.60 (±1.02)	101.60 (±1.02)	6.35 (±0.15)
6	152.4	7.063 (±.060)	6.000 (±.060)	0.250 (±.006)	179.40 (±1.52)	152.40 (±1.52)	6.35 (±0.15)